

## PRESSURE RIVETED COPPER EXPANSION CONNECTORS DIN 46 276 – SERIES GKKN

### Design

The expansion connectors are continuously made of copper foils of a high strength. At the contact ends the foils are riveted with copper sheet and pressed.

### Material

Foils made of SE-Cu, 0.1. to 0.3 mm thick. Cover bar made of E-Cu.

The rivets are made of E-Cu, their dimensions and numbers are according to the cross-section.

### Drillings

Standard design without drillings, on request drillings according to DIN 43 673 or to customer's specification.

Type GKKN – Ordering examples for frequent dimensions					
Order No.	b [mm]	a [mm]	s [mm]	l [mm]	Weight [kg]
GKKN 40/5-230	40	40	5	230	ca. 0,6
GKKN 40/10-230	40	40	10	230	ca. 1,1
GKKN 50/5-230	50	50	5	230	ca. 0,8
GKKN 50/5-280	50	50	5	280	ca. 0,9
GKKN 50/5-300	50	80	5	300	ca. 1,0
GKKN 50/10-280	50	50	10	280	ca. 1,6
GKKN 50/10-300	50	80	10	300	ca. 1,8
GKKN 60/5-280	60	60	5	280	ca. 1,1
GKKN 60/5-300	60	80	5	300	ca. 1,3
GKKN 60/10-280	60	60	10	280	ca. 2,0
GKKN 60/10-300	60	80	10	300	ca. 2,2
GKKN 80/10-300	80	80	10	300	ca. 2,9
GKKN 80/15-280	80	80	15	280	ca. 3,9
GKKN 80/15-300	80	80	15	300	ca. 4,1
GKKN 100/10-320	100	80	10	320	ca. 3,8
GKKN 100/15-320	100	80	15	320	ca. 5,4
GKKN 100/20-320	100	80	20	320	ca. 7,0
GKKN 120/20-320	120	80	20	320	ca. 8,4