

## INERT-GAS WELDED COPPER EXPANSION CONNECTORS DIN 46 276 – SERIES GKKS

### Design

The contact ends are made of flat copper and are inert-gas welded to the connector stacking built up by copper foils.

### Material

Connector stacking: Foils made of SE-Cu, 0.1 to 0.3 mm thick.  
Contact ends: Flats made of E-Cu.

### Drillings

Standard design without drillings, on request drillings according to DIN 43 673 or to customer's specification.

Type GKKS – Ordering examples for frequent dimensions					
Order No.	b [mm]	a [mm]	s [mm]	l [mm]	Weight [kg]
GKKS 40/5-230	40	40	5	230	ca. 0,5
GKKS 40/10-230	40	40	10	230	ca. 0,9
GKKS 50/5-280	50	50	5	280	ca. 0,7
GKKS 50/5-300	50	80	5	300	ca. 0,7
GKKS 50/10-280	50	50	10	280	ca. 1,4
GKKS 50/10-300	50	80	10	300	ca. 1,5
GKKS 60/5-300	60	80	5	300	ca. 0,9
GKKS 60/10-280	60	60	10	280	ca. 1,7
GKKS 60/10-300	60	80	10	300	ca. 1,8
GKKS 80/10-300	80	80	10	300	ca. 2,4
GKKS 80/15-300	80	80	15	300	ca. 3,5
GKKS 100/10-320	100	80	10	320	ca. 3,1
GKKS 100/15-320	100	80	15	320	ca. 4,7
GKKS 100/20-320	100	80	20	320	ca. 6,2
GKKS 120/20-320	120	80	20	320	ca. 7,5